


Absperrpfosten Stahlrohr Ø 60 x 2,5 mm
herausnehmbar ohne Verschluss,
feuerverzinkt, mit 1 Öse



Barrier posts Steel tube Ø 60 x 2,5 mm
removable without locking mechanism, hot-dip
galvanized, with 1 eyelet



Artikelbeschreibung:

Absperrpfosten Stahlrohr Ø 60 x 2,5 mm mit
aufgeschweißter Stahlkappe 900 mm Überflur
herausnehmbar, ohne Verschluss mit
Bodenhülse Typ 460.10 ca. 400 mm Unterflur,
feuerverzinkt, mit 1 Öse

Verwendungszweck:

Absperrpfosten zur Sperrung von Gehwegen
für Fahrzeuge, zur Abgrenzung von Wegen.

Technische Daten:

Gewicht: 7,00 kg/St
Material:
Stahl S235 JR

Oberfläche:
Feuerverzinkung nach DIN ISO 1461

item description:

Barrier posts Steel tube Ø 60 x 2.5 mm with
welded steel cap 900 mm above ground
removable, without locking mechanism with
ground socket part-no. 460.10 approx. 400 mm
below ground, hot-dip galvanized, with 1 eyelet

designated purpose:

Barrier posts for closing off sidewalks for
vehicles, for demarcating paths.

technical specifications:

weight: 7,00 kg/pc
material:
S235 JR

surface:
hot dipped galvanized acc. to DIN ISO 1461