


Absperrpfosten Stahlrohr Ø 76 x 2,6 mm
ortsfest, für Dübelbefestigung, feuerverzinkt
und weiß beschichtet mit drei rot
reflektierenden Leuchtstreifen, mit 1 Öse



Barrier posts Steel tube Ø 76 x 2,6 mm
stationary, to be fixed by plugs, hot-dip
galvanized and white coated with three red
reflecting stripes, with 1 eyelet



Artikelbeschreibung:

Absperrpfosten Stahlrohr Ø 76 x 2,6 mm mit
aufgeschweißter Stahlkappe 900 mm Überflur
ortsfest, für Dübelbefestigung mit Bodenplatte
100 x 150 mm, feuerverzinkt und weiß
beschichtet mit drei rot reflektierenden
Leuchtstreifen, mit 1 Öse

Verwendungszweck:

Zum Sperren, Sichern und Schützen von
Bereichen.

Technische Daten:

Gewicht: 6,00 kg/St
Material:
S235 JR

Oberfläche:
Feuerverzinkt und Pulverbeschichtet

item description:

Barrier post steel tube Ø 76 x 2.6 mm with
welded steel cap 900 mm above ground
stationary, to be fixed by plugs with base plate
100 x 150 mm, hot-dip galvanized and white
coated with three red reflecting stripes, with 1
eyelet

designated purpose:

For stopping, and securing or saving of areas.

technical specifications:

weight: 6,00 kg/pc
material:
S235 JR

surface:
hot dipped galvanized and powder coated