


Absperrpfosten, Stahlrohr $\varnothing 89 \times 2,9$ mm, ortsfest, für Dübelbefestigung, feuerverzinkt, ohne Öse



Barrier posts, steel tube $\varnothing 89 \times 2,9$ mm, stationary, for casting in concrete, hot-dip galvanized, without eyelet



Artikelbeschreibung:

Absperrpfosten, Stahlrohr $\varnothing 89 \times 2,9$ mm, mit aufgeschweißter Stahlkappe, 900 mm Überflur, ortsfest, für Dübelbefestigung, mit Bodenplatte 100 x 150 mm, feuerverzinkt, ohne Öse

Verwendungszweck:

Zum Sperren, Sichern und Schützen von Bereichen.

Technische Daten:

Gewicht: 7,50 kg/St
 Material:
 S235 JR

Oberfläche:
 Feuerverzinkung nach DIN ISO 1461

item description:

Barrier posts, steel tube $\varnothing 89 \times 2,9$ mm, with welded steel cap, 900 mm above ground, stationary, to be fixed by plugs, with base plate 100 x 150 mm, hot-dip galvanized, without eyelet

designated purpose:

For stopping, and securing or saving of areas.

technical specifications:

weight: 7,50 kg/pc
 material:
 S235 JR

surface:
 hot dipped galvanized acc. to DIN ISO 1461