


Absperrpfosten, Stahlrohr 70 x 70 mm, herausnehmbar, mit Dreikantverschluss, feuerverzinkt, ohne Öse



Barrier posts, steel tube 70 x 70 mm, removable, with Euro profile cylinder lock, hot-dip galvanized, without eyelet



Artikelbeschreibung:

Absperrpfosten, Vierkantrohr 70 x 70 mm, mit Stahlkappe, 900 mm Überflur, herausnehmbar, mit Dreikantverschluss nach DIN 3223, oben innenliegend, selbsteinrastende Verriegelung, mit Bodenhülse Typ 470.10, ca. 500 mm Unterflur, feuerverzinkt, ohne Öse

Verwendungszweck:

Zum Sperren, Sichern und Schützen von Bereichen.

Technische Daten:

Gewicht: 12,50 kg/St
 Material:
 S235 JR

Oberfläche:
 Feuerverzinkung nach DIN ISO 1461

item description:

Barrier post, square tube 70 x 70 mm, with steel cap, 900 mm above ground, removable, with triangular locking mechanism acc. with DIN 3223, top inside, self-engaging lock, with ground socket part-no. 470.10, approx. 500 mm below ground, hot-dip galvanized, without eyelet

designated purpose:

For stopping, and securing or saving of areas.

technical specifications:

weight: 12,50 kg/pc
 material:
 S235 JR

surface:
 hot dipped galvanized acc. to DIN ISO 1461