


Absperr-Stilpfosten, Serie 484B, Ø 82 mm, herausnehmbar, selbsteinrastende Verriegelung, inkl. Bodenrosette, mit feuerverzinkter Bodenhülse Typ 470.10



Ornamental bollard, Series 484B, Ø 82 mm, removable, self-engaging lock, including ground rosette, with hot-dip galvanized ground, socket part-no. 470.10



Artikelbeschreibung:

Stilpoller, aus Stahlrundrohr Ø 82 mm, ca. 900 mm Überflur, feuerverzinkt und beschichtet, Farbe: RAL 9005 matt (mattschwarz), herausnehmbar, selbsteinrastende Verriegelung, inkl. Bodenrosette, mit feuerverzinkter Bodenhülse Typ 470.10, ca. 500 mm Unterflur, mit Dreikantverschluss nach DIN 3223, ohne Öse

Verwendungszweck:

Zum Sperren, Sichern und Schützen von Bereichen.

Technische Daten:

Gewicht: 13,50 kg/St
Material:
S235 JR

Oberfläche:
Feuerverzinkt und Pulverbeschichtet

item description:

Ornamental bollard, of round steel tube Ø 82 mm, approx. 900 mm above ground, hot-dip galvanized and coated, color: RAL 9005 matt (jet black), removable, self-engaging lock, including ground rosette, with hot-dip galvanized ground socket part-no. 470.10, approx. 500 mm below ground, with triangular locking mechanism acc. with DIN 3223, without eyelet

designated purpose:

For stopping, and securing or saving of areas.

technical specifications:

weight: 13,50 kg/pc
material:
S235 JR

surface:
hot dipped galvanized and powder coated