

Absperr-Stilpfosten, Serie 482B, Ø 82 mm, umlegbar, selbststeinrastende Verriegelung, zum Einbetonieren

Ornamental bollard, Series 482B, Ø 82 mm, foldable, self-engaging lock, for casting in concrete



Artikelbeschreibung:

Stilpoller, aus Stahlrundrohr Ø 82 mm, ca. 900 mm Überflur, feuerverzinkt und beschichtet, Farbe: DB703, umlegbar, selbststeinrastende Verriegelung, zum Einbetonieren, mit feuerverzinkter Bodenhülse Typ 470.60, ca. 400 mm Unterflur, mit Profilzylinderschloss und drei Schlüsseln, ohne Öse

Verwendungszweck:

Zum Sperren, Sichern und Schützen von Bereichen.

Technische Daten:

Gewicht: 13,00 kg/St
Material:
S235 JR

Oberfläche:
Feuerverzinkt und Pulverbeschichtet

item description:

Ornamental bollard, of round steel tube Ø 82 mm, approx. 900 mm above ground, hot-dip galvanized and coated, color: DB703, foldable, self-engaging lock, for casting in concrete, with hot-dip galvanized ground, socket part-no. 470.60, approx. 400 mm below ground, with Euro profile cylinder lock and three keys, without eyelet

designated purpose:

For stopping, and securing or saving of areas.

technical specifications:

weight: 13,00 kg/pc
material:
S235 JR

surface:
hot dipped galvanized and powder coated