



Universalbügel aus Stahlrohr Ø 76 x 2,6 mm, zum Einbetonieren



Universal hoop of steel tube Ø 76 x 2,6 mm, for casting in concrete



Artikelbeschreibung:

Universalbügel aus Stahlrohr Ø 76 x 2,6 mm, Gesamtbreite: 400 mm, Gesamthöhe: 1000 mm, feuerverzinkt

Verwendungszweck:

Zum Sperren, Sichern und Schützen von Bereichen.

Technische Daten:

Gewicht: 8,00 kg/St

Material: S235 JR

Oberfläche:

Feuerverzinkung nach DIN ISO 1461

item description:

Universal hoop of steel tube Ø 76 x 2.6 mm, total width: 400 mm, total height: 1000 mm, hot-dip galvanized

designated purpose:

For stopping, and securing or saving of areas.

technical specifications:

weight: 8,00 kg/pc

material: S235 JR

surface:

hot dipped galvanized acc. to DIN ISO 1461

^{*}Alle Angaben sind Richtwerte (teilweise mit branchenüblichen Rundungen zum besseren Verständnis) und dienen leidglich zum Produktverständnis, nicht aber als Basis zum Bau von Zubehörteilen, Lagergestellen, Adaptierungen, Kombinationsprodukten oä. Alle Angaben sind ohne Gewähr, für evtl. Fehler und resultierende Folgen übernehmen wir keine Verantwortung.
*All data are approximate values (partly with industry-standard rounding for better understanding) and serve only for product understanding, but not as a basis for the design of accessories, storage solutions, adaptations, combination products or the like. All information is without guarantee, for possible errors and resulting consequences we assume no responsibility.