


Höhenbegrenzer drehbar zum Einbetonieren,
Querrohrlänge: 4000 mm, für Vorhangschloss, für
Dübelbefestigung

Height restriction barrier for casting in concrete, cross
tube length: 4000 mm, for padlock, to be fixed by plugs



Artikelbeschreibung:

Höhenbegrenzer zum Einbetonieren
Horizontal schwenkbar, mit Seilzugverstärkung,
Verriegelung geschlossen oder geöffnet mit
Bolzen, vorgerichtet für Vorhangschloss oder
mit Dreikantverschluss nach DIN 3223 bzw.
Profilzylinderschloss, weiß beschichtet
mit rot reflektierenden Leuchtbstreifen
1-teilig
Drehpfostenm aus Stahlrohr Ø 102 mm
Querrohr aus Aluminium 100 x 50 mm
Durchfahrthöhe variabel einstellbar
ca. 1800 mm - 2800mm
Gesamthöhe Überflur ca. 3000 mm, Querrohrlänge:
4000 mm, für Vorhangschloss, für Dübelbefestigung

item description:

Height restriction barrier
for casting in concrete
pivotable horizontally, with cable pull, lock
closed or opened by pin, prepared for padlock
or with triangular locking mechanism acc. to
DIN 3223 or Euro profile cylinder lock, white
coated with red reflecting stripes, cross tube length: 4000
mm, for padlock, to be fixed by plugs

technical specifications:

weight: 0,00 kg/pc

Technische Daten:

Gewicht: 0,00 kg/St